



gtRootbarrier Joining Tape

gtRootbarrier® Joining Tape is a double sided solvent free rubber resin supplied on an easily removable liner.

Benefits of Product:

- Clean, easy to use alternative to brush adhesives
- Very aggressive pressure sensitive adhesive
- Non-hardening and permanently flexible
- Forms a strong waterproof bond
- Excellent bond strength
- No curing time required
- Solvent free, therefore no fumes
- Versatile 'instant stick' adhesive on a roll

Technical Properties:

Description	Units	Nominal Value	Test Method
Specific Gravity	g cm ⁻³	0.98	55295*
Softening Point (Ring and Ball)	°C	85	55272*
Cohesion	N mm ⁻²	0.6	55270*
Tack (Rolling Ball Method)	mm	30	55233*
Service temperature	°C	0-40	-

*Scapa Internal Test Method

Note: Should not be used where good chemical or UV resistance is required.

Standard Presentation:

- Roll length - 30m (0.4mm)
- Roll width - 19mm,
- Packaging - Bulk packed

Recommendations:

It is recommended that this product is applied at temperatures over 10°C

To aid the cutting of product, it is advisable to dip blades or scissors into water immediately prior to use.

The rolls should be stored flat on their edges in the original packaging until required for use.

The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes.

Service life may vary with conditions of use and is affected by climatic environment, but should not be less than one year from date of manufacture, if stored in a moderate climate and good conditions.

Green-tech endeavour to ensure that the information given on this technical data sheet is accurate, but accept no liability for its use or its suitability for particular application.

Rabbit Hill Business Park, Great North Road, Arkendale, Knaresborough HG5 0FF

T: 01423 332100 E: sales@green-tech.co.uk W: www.green-tech.co.uk Facebook: @greentechuk Twitter: @greentechltd